

T-SERIES ECU

T8



- Dual wideband Lambda control
- Up to 12 cylinders
- 28 inputs
- 28 outputs
- 9 control strategies
- IP67 billet aluminium case

The T8 is ideal for fully sequential 6 or 8 cylinder engines but can also run 12 cylinder engines semi-sequentially. The T8 features dual wideband lambda and dual variable cam control making it a great choice for V engines. It also has 4 wheel speed inputs to allow for more advanced traction control, including wet/dry modes.

T-Series engine control units are powered by an all-new, automotive specific, multi-core processor. They feature Bosch lambda controllers for maximum accuracy, multiple safety redundancies, high resolution map tables, fully configurable I/O and up to 32Mb of up to 1Khz logging with compression algorithms for fast log downloads. The PC software has a user-friendly, responsive design for better readability on high resolution monitors using high scaling (DPI). It features a full oscilloscope for crankshaft/camshaft signal analysis and allows firmware to be upgraded without special cables or separate software.

INPUTS

Analogue (0-5v)	12
Digital	6
Thermistor (NTC)	3
Wheel Speed	4
Wideband Lambda	2
Knock	0

OUTPUTS

Digital (PWM)	10
Coil Drivers	8
Injector Drivers	8
Cam Solenoid Drivers	2
H-Bridge (FBW) Drivers	0

COMMUNICATIONS

USB	For PC connection
Serial	For dyno box connection
CAN bus	For communication with dashboards, power distribution modules, dataloggers etc.

CONTROL STRATEGIES

Auxiliary PWM Control	✓
Pit Limiter	✓
Launch Control	✓
Flat-shift Control	✓
VTEC Control	✓
Boost Control	✓
Idle Control	✓
Wideband Lambda	dual
Variable Cam Control	dual
Traction Control	✓
Wet/Dry Traction	✓
Fly-by-wire Control	X
Knock Control	X
Paddle-shift Control	X

MISC

Dimensions	188x176x25-42mm
Weight	894g
Material	billet aluminium
Ingress Protection	IP67
Hardware Upgradeable	To T8+/T12/T12+